

SGE1-D Series		Magnetic Starter	
Standard		IEC60947-4-1 / IEC60439-1	
Electric ratings		09-95A	
Rated operating voltage Ue(V)		Up to 690	
Rated insulation voltage Ui(V)		690	
Rated impulse withstand voltage Uimp(kV)		8	
Rated frequency(Hz)		50/60	
Control buttons		Green Start button	
		Red Stop/Reset button	
Enclosure		SGE1-D09/12/18 Frame Double insulated,IP 65	
		SGE1-D25/32 Frame Double insulated,IP 65	
		SGE1-D40/50/65/80/95 Frame Metal, IP 65	
Electrical life		0.5 million	
Mechanical life		5 million	
Matched AC Contactor type		SGC1-D series	
Matched Thermal relay type		SGR2-D series	
Ambient air temperature		-5 to+40,max.95%humidity	
Storage temperature		-40~+75	
Maximum operating altitude(meters)		≤2000	
Certification		CE	



SGE1-D25





SGE1-D40

SGE1-D Series

Magnetic Starter

Type	Matched items		Rated power AC-3(KW)				
	Thermal relay	AC contactor	220/230V	380/400V	415V	440V	660/690V
SGE1-D25	SGR2-D13	SGC1-D25	5.5	11	11	11	15
SGE1-D32	SGR2-D23	SGC1-D32	7.5	15	15	15	18.5



Type	Matched items		Rated power AC-3(KW)				
	Thermal relay	AC contactor	220/230V	380/400V	415V	440V	660/690V
SGE1-D40	SGR2-D33	SGC1-D40	11	18.5	22	22	30
SGE1-D50	SGR2-D33	SGC1-D50	15	22	25	30	33
SGE1-D65	SGR2-D33	SGC1-D65	18.5	30	37	37	37
SGE1-D80	SGR2-D33	SGC1-D80	22	37	45	45	45
SGE1-D95	SGR2-D33	SGC1-D95	25	45	45	45	45

